





The SSI Series submersible pumps feature a stainless steel construction for durability in demanding applications and stainless steel impellers and diffusers for long-lasting performance and reliability. Its I-Blade technology offers stronger hydraulic components for improved efficiency, while tungsten inert gas (TIG) progressive welding creates stronger bonds.

### **FEATURES**

- High-Volume Solution: Features flows up to 1300 gpm to meet high-volume pumping application demand
- Simple, Modern Design: Stamped stainless steel pump family is fully serviceable
- Unique Construction: I-Blade technology, exclusive to Franklin Electric, increases the structural integrity of the pump's internal components, pumping more water per horsepower and improving efficiency when compared to traditional impeller designs
- Rugged: Utilizing tungsten inert gas (TIG) progressive welding, the metal materials are mixed during the process, creating a stronger bond for durability in harsh environments
- Reliable: Integrated check valves eliminate back flow, and round shafts increase durability in abrasive environments
- Easy Sizing: FE Select allows for simplified sizing, quoting, and product identification
- Availability: Build Center Program capability allows for speedier delivery time from distributors to contractors
- Franklin Electric Build Centers require a total of four individual part numbers to build all Franklin Electric strapped turbines, providing you with the flexibility to design and build to your customers' needs
- Fully Supported: Comes fully supported by the Industry's leading Technical Support professionals and Field Service Engineers
- Comprehensive Training: Step by step build instructions to ensure a quality build every time

#### **APPLICATIONS**

- Irrigation
- Municipal
- De-watering

- Agricultural
- Commercial

### TECHNICAL SPECIFICATIONS


Description	6"	8"	10"
Flow	85-400 gpm	345-580 gpm	500-1300 gpm
HP	5-60	25-125	40-250
Efficiency	Max 80%	Max 78%	Max 80%
Discharge	3"& 4" NPT	5" NPT	6" NPT
Motor Size	4" & 6"	6" & 8"	6", 8", & 10"





# **SSI SERIES STAINLESS STEEL SUBMERSIBLE PUMPS**

## PERFORMANCE



## 6" SSI SERIES PUMP ENERGY INDEX

Basic Model	PEI <sub>cL</sub> Number	
85SSI	0.85	
150SSI	0.93	
225SSI	0.88	
260SSI	0.90	
300SSI	0.95	

3



PIK Avenue Mall, Lantai 6, Jl. Pantai Indah Barat No. 1, Kamal Muara, Penjaringan, Jakarta Utara 14470 Tel: +62 21 22674247

submersiblepump.co.id

